

STEEL FORGED UNIVERSAL CLAW COUPLING (HOSE END)



These are made of Drop Forged steel and hardened to resist rough handling in the course of use. Suitable for quick jointing and dismantling of Hoses. Available in 3/8" to 1" sizes. Part No. Series DHE

BALL VALVE (AIR COCK)



Body made of ferrous and non-ferrous metal & fitted with stainless steel ball to prevent air leakage. It is also fitted with steel forged and specially locked handle for on and off operation. Available in sizes 1/2" to 2". Part No. Series ACC

HOSE CLAMP (MALLEABLE CASTING)



These are designed to give a compact joint between Hose and Nipple. Available in 1/2" to 3" sizes. Part No. Series DFC

STEEL FORGED UNIVERSAL CLAW COUPLING (MALE)



These are made of Drop Forged steel with outside (male) thread having standard claw and can be fitted (mated) with Hose End and Female of all sizes available in 3/8" to 1" sizes. Part No. Series DFM

STEEL FORGED UNIVERSAL CLAW COUPLING (FEMALE)



Made of Drop Forged steel having inside (female) thread. Available in 3/8" to 1" sizes. Part No. Series DFF

VICTAULIC COUPLING (MALLEABLE)



For quick laying of Air line with no chance of Air leakage. Available in sizes 2" to 8". Part No. Series VFD

CONNECTOR & ADAPTER



Having both side 8 TPI BSW threads. Can be fitted with RDT or RDC series couplings of sizes 3/4" to 2" Part No. Series CON

(FEMALE)

Having BSP Female threads and can be fitted with 8 TPI BSW RDC connector. Available in sizes 3/4" to 2" Part No. Series ADF

4 BOLT CLAMP



(HEAVY DUTY)

Made of malleable steel casting. Recommended for high pressure. Available in sizes : 1-1/2" to 2" only. Part No. Series HDC

VICTAULIC WASHER



Made of neoprene rubber to be fitted between two victaulic pipes having standard grooves before clamping of VICTAULIC COUPLING. Available in sizes 2" to 8". Part No. Series VRW

HOSE JOINTING NIPPLES



For economical Hose jointing and designed to lock edges at both ends. Available in sizes ranging from 3/8" to 3". Part No. Series HJN

PACKING



Made of heat and oil resistant synthetic rubber. Required to be used with each of above Claw Coupling ranging from 3/8" to 2" sizes. Part No. Series PAC